

Think Sustainable!

All paper based packaging elements of our self-adhesive graphics products are 100% recyclable where appropriate paper waste recycling bins are available, and many are already made from recycled content, including inner cores, packaging boxes and plastic core stoppers. Check local recycling guidelines to recycle our packaging!

For more information about Mactac Sustainability commitment please visit the Mactac Graphics website: mactacgraphics.eu/sustainability

©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

All Mactac statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Mactac products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Mactac products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

2025_32863 EN





contact.mactac@mactac.eu | mactacgraphics.eu



Mactac
Digital Quick Portfolio Guide

Overlamine
Products

(2/2)

Application		Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish				Adhesive	Liner	Durability*	Conform- ability	Outdoor application	Fire certification EN 13501-1
					Clear	Glossy	Matt	Satin	Optically clear	Textured	Permanent	UV inks compatible	Type	
Floor Graphics**														
Short term floor application		LUV 70300		125	●		●		●	●	CK	6 mths	1D	Bfl-s1
		LUV 6301		100	●		●		●	●	CK	3 mths	1D	Bfl-s1
		FloorGrip		150	●		●		●	●	CK	Indoor: 1yr Outdoor: 3mths	1D	Bfl-s1
		StreetLam		385	●			●	●	●	CK	6 mths	2D	Bfl-s1
Special Laminating films														
Anti-graffiti application		LUV 7036	🌱	36	●	●			●	●	PET	3 yrs	1D	B-s1,d0
		LAG 100	🌱	60	●			●	●	●	CK	5 yrs	2D+	B-s1,d0
Anti-graffiti/ photographs		PG 7075	🌱	75	●	●			●	●	PET	3 yrs	1D	B-s1,d0
Photographics		PG 7285		70	●		●		●	●	CK	4 yrs	1D	C-s1, d0
PermaFun Series		Brushed Metal		100	●				●	●	CK	5 yrs	2D	B-s1,d0
Whiteboard application		PG 7034	🌱	30	●	●			●	●	PET	2 yrs	1D	na

* For more information pleas refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films.
** All Floor Graphics products are EN 13036-4 Anti-slip certified.

Overlamine
Products

(1/2)

Application		Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish				Adhesive	Liner	Durability*	Conform- ability	Outdoor application	Fire certification EN 13501-1
					Clear	Glossy	Matt	Satin	Optically clear	Textured	Permanent	UV inks compatible	Type	
Vehicle wrapping														
Long term application on curved surfaces		LF 10700 CG-UV		30	●	●			●	●	CK	6 yrs	3D	B-s1,d0
		LF 10700 CM-UV		30	●		●		●	●	CK	6 yrs	3D	B-s1,d0
		LF 10500 CG		50	●	●			●		PET	5 yrs	2D+	B-s1,d0
Curved surfaces														
Long term application for curved surfaces		LF 9700 CG-UV		80	●	●			●	●	CK	5 yrs	2D	B-s2,d0
		LF 9700 CM-UV		80	●		●		●	●	CK	5 yrs	2D	B-s2,d0
		LF 9500 CG-UV		70	●	●			●	●	CK	4 yrs	2D	B-s1,d0
Medium term application for slightly curved surfaces		LF 9500 CM-UV		70	●		●		●	●	CK	4 yrs	2D	B-s1,d0
		LF 9300 CG-UV		80	●	●			●	●	CK	3 yrs	2D	B-s1,d0
		LF 9300 CM-UV		80	●		●		●	●	CK	3 yrs	2D	B-s1,d0
		LF 9300 CS-UV		80	●			●	●	●	CK	3 yrs	2D	B-s1,d0
Flat to slightly curved surfaces														
Medium term application for slightly curved surfaces		LF 8700 CG-UV		80	●	●			●	●	CK	3 yrs	1D	B-s1,d0
		LF 8700 CM-UV		80	●		●		●	●	CK	3 yrs	1D	B-s1,d0
		LF 8700 CS-UV		80	●			●	●	●	CK	3 yrs	1D	B-s1,d0
Short term application for flat surfaces		LF 8500 CG		70	●	●			●	●	CK	2 yrs	1D	B-s1,d0
		LF 8500 CM		70	●		●		●	●	CK	2 yrs	1D	B-s1,d0
		LF 8510 CS PP	🌱	60	●			●	●	●	CK	5 yrs	2D+	B-s1,d0



Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish								Adhesive						Liner	Durability*		Conformability	Compatible ink tech.			Outdoor application	Fire certification EN 13501-1	Overlaminates				
				White	Clear	Translucent	Glossy	Matt	Satin	Textured	Perforated	High Tack	Permanent	Removable	Semi-Permanent	Bubble-free	Dot	Grey	Transparent	Black	Type	Unprinted	Printed + Laminated		Latex	UV	Solvent				
Vehicle wrapping																															
Long term application on curved surfaces	JT 10800 WG-BFG		50	●			●					●				●		●			PE	7 yrs	5 yrs	3D		●	●	●	●		LF 10700 CG-UV / LF 10700 CM-UV
	JT 10700 WG-BFG		50	●			●					●				●		●			PE	7 yrs	5 yrs	3D		●	●	●	●	B-s1,d0	
	JT 10500 WG-BFG		55	●			●						●				●		●			PE	7 yrs	4 yrs	2D+		●	●	●	●	
Curved surfaces																															
Long term application on curved surfaces	JT 9700 WG-PG		80	●			●					●						●			PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	LF 9700 UV Series
	JT 9700 WG-PT		80	●			●					●						●	●		PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	
	JT 9700 WG-BFG		80	●			●					●				●		●			PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	
	JT 9700 CG-PT		80		●		●					●				●		●			PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	
	JT 9700 CG-BFT		80		●		●					●				●		●			PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	
	JT 9700 WT-PT		80	●		●						●						●	●		PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	
	LF 9500 Series	JT 9700 WG-HTT		80	●			●				●							●	●		PE	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0
		JT 9500 WG-PG		65	●			●					●						●			CK	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0
		JT 9500 WG-PT		65	●			●					●						●	●		CK	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0
		JT 9500 WG-BFG		65	●			●					●				●		●			CK	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0
		JT 9500 WM-PG		65	●				●				●						●			CK	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0
		JT 9500 CG-RT		65		●		●						●					●	●		CK	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0
Medium term application on slightly curved surfaces	JT 9300 WG-PG		80	●			●					●						●			PE	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	LF 9300 UV Series
	JT 9300 WG-PT		80	●			●					●						●	●		PE	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	
	JT 9300 WG-RG		80	●			●					●	●					●			PE	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	
	JT 9300 WG-BFG		80	●			●					●				●		●			PE	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	
	JT 9300 CG-PT		80		●		●					●							●		PE	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	
Flat surfaces																															
Medium term application on flat surfaces	JT 8700 WG-PG		90	●			●					●						●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	LF 8700 UV Series
	JT 8700 WG-RG		90	●			●							●				●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	
	JT 8700 WM-PG		90	●				●				●						●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	
	JT 8700 WM-RG		90	●				●						●				●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	
	JT 8700 CG-RT		75		●		●							●					●		CK	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	
	JT 8700 WT-PT		80	●		●						●							●		CK	4 yrs	2 yrs	1D		●	●	●	●	B-s2,d0	
	JT 5826 P		90	●				●				●							●		CK	3 yrs		1D		●		●	●	na	
Short term application on flat surfaces	JT 8510 WM-PG PP	🟢	90	●				●				●						●			CK	3 yrs		1D		●	●		●	B-s1,d0	LF 8500 Series
	JT 8500 WG-PG		95	●			●					●						●			CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WG-PT		95	●			●					●						●	●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WG-RG		95	●			●						●					●			CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WG-RT		95	●			●							●					●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WG-SPB		90	●											●				●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WG-BFT		95	●			●									●			●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WM-PG		95	●			●					●							●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WM-PT		95	●				●					●						●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WM-RG		95	●				●						●					●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WM-RT		95	●				●						●					●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 WM-HTT		95	●				●			●								●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	JT 8500 CG-RT		95		●		●							●					●		CK	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0	
	Easy 209 P WG-PG		200	●				●					●						●		CK	2 yrs	1 yr	1D		●	●	●	●	B-s1,d0	
	Easy 209 P WG-PT		200	●				●					●							●	CK	2 yrs	1 yr	1D		●	●	●	●	B-s1,d0	
	Dot Series																														
Short term promotional graphics on flat surfaces	JT 8300 WM-RT Dot		120	●				●						●			●		●		CK	1 yr		1D		●	●	●		B-s2,d0	
	JT 8300 CG-RT Dot		120		●		●							●			●		●		CK	1 yr		1D		●	●	●		B-s2,d0	
	JT 8300 WM-RT Dot Floor**		200	●				●						●				●		●	CK	3 mths	1 mth	1D		●	●	●		Bfl-s1	
Floor Graphics																															
Promotional graphics on floors	StreetRap		70	●				●				●							●		PE	6 mths	6 mths	2D+		●	●	●	●	Bfl-s1	StreetLam / FloorGrip
Window Graphics																															
Perforated Window Films	JT 7301 WG-PB 40		160	●			●				●			●				●			PE	1 yr	2 yrs	1D		●	●	●	●	B-s2,d0	LUV 7036/ LF 10500 CG
	JT 7302 WG-PB 30		160	●			●				●			●				●			PE	1 yr	2 yrs	1D		●	●	●	●	B-s2,d0	
	JT 7501 WG-PB 40		160	●			●				●			●				●			PE	3 yrs	3 yrs	2D		●	●	●	●	B-s1,d0	
Long term window films	JT 9700 WT-BFT Frosted		80			●		●				●						●			PE	5 yrs		2D		●	●	●	●	na	
	JT 9700 WT-BFT Dusted		80			●		●				●						●			PE	5 yrs		2D		●	●	●	●	na	
Medium term window films	JT 6710 CG-RT PET	🟢	50		●		●						●					●		PET	2 yrs	2 yrs	1D		●	●		●	B-s1,d0	LUV 7036	
Architectural Wall Application																															
Exterior Wall application	WW 309		100	●			●					●						●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s1,d0	LF 8700 UV Series / LUV 7036 / LAG 100 / LUV 6300 / FloorGrip / PG 7285
	WW 300		100	●				●				●						●			CK	4 yrs	3 yrs	1D		●	●	●	●	B-s1,d0	
	WW 319 PU Gloss	🟢	80	●			●					●						●			PE	5 yrs	5 yrs	1D		●	●	●	●	B-s1,d0	
	WW 100 Pro		55	●			●					●						●			PE	3 yrs	3 yrs	2D+		●	●	●	●	B-s1,d0	
Interior Wall application	WW Canvas		250	●				●		●			●					●			CK	3 yrs		1D		●	●	●		B-s2,d0	LF 10700 UV Series / LF 10500 CG / LAG 100
	WW Veneziano		300	●				●		●			●					●			CK	3 yrs		1D		●	●	●		B-s2,d0	
	WW Leather		225	●				●		●			●					●			CK	3 yrs		1D		●	●	●		B-s2,d0	

★★ All Floor Graphics products are EN 13036-4 Anti-slip certified.