

## JT 8300 WM-RT Dot Floors

### PRODUCT DESCRIPTION

Monomeric calendered self-adhesive floor graphic print media with dotted adhesive.

**Face Material:** 200 µm white matt PVC

**Adhesive:** Emulsion acrylic removable transparent dotted

**Liner:** Clay coated 120 g/sqm

### TYPICAL USE

Short-term indoor promotional graphics on flat smooth floor surfaces.

### PROCESSING

Especially designed for solvent based, eco-solvent, mild solvent, Latex and UV\* inkjet printing on wide-format printing equipment.

JT 8300 WM-RT Dot Floors should not be laminated.

To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used.

Profiles can be obtained from our subsidiaries or distributors, or can be downloaded from: [www.mactacgraphics.eu](http://www.mactacgraphics.eu).

For further information on printing, application and removal, please refer to "TB 5.1 Application of Mactac JT 8300 Dot Floors".

\*Not compatible with UV-Gel inks

To ensure application suitability, always test the proposed construction under actual application and end-use conditions before going into full production.

### SHELF LIFE

2 years when stored at 15 to 25°C and ± 50 % relative humidity (in the original packaging).

### PHYSICAL PROPERTIES (TYPICAL VALUES)

#### Average Values Test Method

Thickness		
Face (microns)	200 µm	ISO 534
Adhesive data, 23°C (N/25 mm)		
Peel adhesion on glass		
- Quick tack	4	FTM9
- 24 hour residence	2	FTM1
Dimensional stability		
Shrinkage (48 hours at 70°C applied on Aluminium)	Max. 1.0 mm	FTM14
Shrinkage on liner (72 hours at 60°C)	Max. 2.3 mm	Internal method
Temperature ranges		
Minimum application temperature (°C)	+ 10°C	
Service temperature range (°C)	- 20°C to + 70°C	
Certifications		
Fire Classification	Bfl-s1	EN13501-1
Slip Resistance (unprinted and printed)*	PTV 91	EN13036-4

\* For more information on printed Slip Resistance refer to "TB 5.1 Application of Mactac JT 8300 Dot Floors".

### EXPECTED DURABILITY

#### Central Europe Zone 1

Unprocessed	3 months	ISO 4892-2
Printed and applied	1 month	ISO 4892-2

Note: Exposure to heavy cleaning performed with brushes, chemicals and machines will affect the durability of the product and probably cause faster degradation of the inks.

Always test the product to ensure end-use performance.

DISCLAIMER

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.