

# **PERMAfun Brushed Metal**

#### PRODUCT DESCRIPTION

Premium polymeric laminating film with a satin fine Brushed Metal texture.

**Face Material:** 100 µm clear satin textured PVC **Adhesive:** Solvent acrylic permanant transparent

Liner: Clay coated 135 g/sqm

#### **TYPICAL USE**

Laminating film specifically designed for mediumterm indoor and outdoor applications on flat and slightly curved surfaces in order to:

- retard colour fade and protect printing media against UV radiation and abrasion
- enhance colours of the prints
- customize the media with homogeneous unique texture finish

Suitable for interior decoration: displays, Point of Sale, hotel decoration.

#### **PROCESSING**

Specifically designed for media printed with Solvent, Eco-solvent, mild-Solvent, Latex and UV-curable inks.

For specific settings of the laminator, please consult the technical manual that comes with the laminator from the original supplier.

For outdoor use, care should be taken to prevent water penetration from the sides of the laminates.

The printed media should be perfectly dry prior to lamination and be left to dry for at least 24h.

Mactac Laminating media must be applied following the instructions in TB 4.1 "Guidelines on handling, converting and applying Mactac Digital media", available from the resource section at www.mactacgraphics.eu.

#### SHELF LIFE

2 years when stored at 15 to 25°C and ± 50 % relative humidity (in the original packaging).

# PHYSICAL PROPERTIES (TYPICAL VALUES) Average Values Test Method

Thickness							
Face (microns)	100 µm			ISO 53	ISO 534		
Adhesive data, 23°C (N/25 mm) Peel adhesion on glass							
- Quick tack		15		FTM9			
- 24 hour residence		18		FTM1			
Dimensional stability							
Shrinkage (48 hours at 70°C applied on Aluminium)	Max. 0.5 mm		FTM14				
Temperature ranges							
Minimum application temperature (°C)					+ 5 °C		
Service temperature range (°C)					- 45°C to + 70°C		
Certifications							
Fire Classification	B-s1, d0 EN13501-1						

## **EXPECTED DURABILITY**

## **Central Europe Zone 1**

Processed*	Up to 5 years	ISO 4892-2
------------	---------------	------------

\*For more information, refer to "TB 7.5 Outdoor Durability of Mactac Graphics - Self-adhesive films".

Note: Overlamination of the inkjet-printed material delays the eventual colour fading that may occur over time. This colour fading is dependent on the quality of the inkjet inks, the orientation of the printed material, the angle of display and the exact geographical location of exposure.

Exposure to severe temperatures, ultraviolet light, and/or conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitudes and south-facing exposure.



#### DISCLAIMER

For more information on the durability and exposure please visit the "Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Selfadhesive films" on the www.https://www.mactacgraphics.eu website.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see

http://terms.europe.averydennison.com. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

